



UD 30 – Safety Spectacle

STANDARD :  IS 5983, ANSI Z87.1, EN 166, CE

INDUSTRY

Construction & projects
Cement
Automotive
Power & utilities
Metals & minings

IDEAL APPLICATIONS

Material handling
Dusty area
Assembly line
Packaging
Medical applications

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Wrap around
Nose piece	Polycarbonate	Universal fit, integral to lens
Temple	Polycarbonate	Spatula type with side protection

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K	50 g.

FEATURES

Polycarbonate lens with polycarbonate temple

Wraparound lens provides perfect impact protection around the eyes

Hard coating on lens

Lens filters out 99.9% of harmful UV light

Over the spectacle safety eyewear

Integral ventilated side shield protection

Soft temple tips

Incredibly light, resilient & durable protective eyewear for all day wear

Fashionable design resembles spectacle, suitable for both men and women

Suitable for different work environment

APPLICATION

Protects eyes exposed to low-level impacts

Best used for protection against flying small fragments

STORAGE

Can be stored in the dark for up to 2years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING

Clean it with the soft cloth

PACKING

100 pieces per carton