



UD 49- Safety Goggles

STANDARD :  IS 5983:1980

INDUSTRY

Chemical
Pharmaceutical
Oil & gas
Iron & steel
Automotive

IDEAL APPLICATIONS

Chemical handling
Labs
Paint shop
Grinding
Medical application

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



CHEMICAL SPLASH PROTECTION



MEDIUM IMPACT RESISTANT



OVER THE SPEC

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	Single & cylinder lens
Frame	PVC / vinyl	Flexible fitting goggle with 4 point ventilation system
Nose piece	PVC	Universal integral to frame
Head band	Textile elastic	Adjustable elastic

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	WEIGHT
Polycarbonate	1	2-1.2	B (120m/s)	75 g.

FEATURES

Polycarbonate lens with soft PVC or vinyl frame

Fully adjustable headband attached to fits most users

Soft frame conforms to facial contours for restful & long time use

Lens filters out 99.9% of harmful UV light

Lens provides medium velocity impact & splash protection around the eyes

Universal fit soft nose bridge conforms to facial contours to ensure a comfortable fit

4 point venting system that circulates air, yet prevent dust

Over the glass protective eyewear for all day wear

Suitable for different work environment & for both men and women

APPLICATION

Protects eyes exposed to medium level impacts

Best used for protection against flying small fragments, liquid splashes, fumes, sparks etc.

Also protects against irritating mist and potentially infectious materials (Lab environment)

STORAGE

Can be stored in the dark for up to 2years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING

	PACKING
Clean it with the soft cloth	100 pieces per cartoon