



UD 71 – Safety Spectacle

STANDARD : IS 5983, ANSI Z87.1, EN 166, CE

INDUSTRY

Construction & projects
Cement
Automotive
Power & utilities
Metals & minings

IDEAL APPLICATIONS

Material handling
Dusty area
Assembly line
Packaging
Medical applications

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens Nose piece	Polycarbonate	9.75 base curve, wrap around design w/side protection
Temple Hinge	Polycarbonate	Universal, integral to lens
Screw	Polycarbonate	Spatula
	Polycarbonate	5 barrel type
	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K	20 g.

FEATURES

Polycarbonate temple with polycarbonate lens
Snug-fitting wrap around lens provides perfect impact protection around the eyes
Hard coating on lens
Lens filters out 99% of harmful UV light
Close-fitting unitary front with dual 9.75 base curvature offers wide and unobstructed vision
Soft temple tips
Incredibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

APPLICATION

Protects eyes exposed to low-level impacts
Best used for protection against flying small fragments

STORAGE

Can be stored in the dark for up to 2years
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING

Clean it with the soft cloth

PACKING

100 pieces per carton

303/307 samuel street abhishek bld
office no G -6 grd floor Masjid bunder
(w) Mumbai Maharashtra 400003

E-mail : safety.vcare@gmail.com

Tel. : +91 9820734624