



## UI 1211 – Safety Helmet

STANDARD : IS 2925:1984, DGMS Approved

### INDUSTRY

Iron & steel  
Cement  
Automotive  
Power & utilities  
Metals & mining

### IDEAL APPLICATIONS

Construction & projects works  
Material handling  
Shop floor  
Packaging  
Maintenance

### SPECIAL FEATURES



LIGHT WEIGHT



RECYCLABLE



STRONG & DURABLE



TEMPERATURE RESISTANT



RATCHET FIT

### COLOURS:

White Blue Yellow Red Green Orange Black

COMPONENT	MATERIAL	ADVANTAGES
Shell Peak Brim	HDPE (High density poly ethylene)	Resistant to high level impact
Cradle Head	HDPE HDPE Plastic Plastic	48 mm, peak protects eye & face from falling objects
band Sweat	Brushed cloth on foam Nylon	Rim around the shell, drains rain water
band Chin strap	Nylon Plastic	6-point adjustment, perfect load distribution
Chin strap clip		Universal fit, dia. 53 cm – 61 cm
Nape strap		Sweat absorbent, long time use
		Holds the shell, universal fit
		Attachment between shell and chin strap
		Fully adjustable, smooth & universal slip fit

### FEATURES

Shell made of HDPE compound  
Dome shape to provide complete coverage  
Smooth finish – solid colour resin for a permanent, no-chip, no-peel finish  
Greater impact resistance and crack resistance  
6-point plastic / textile suspension with slip fit or ratchet fit adjustment  
Adjustable chin strap for customized fit and comfort  
High quality sweat band provides comfort  
Radiant heat resistivity higher than ABS helmets yet light weight  
Designed for use in industries where there is a hazard, which can damage skull

### APPLICATION

Protects head from falling objects  
Protects splashes, spatters etc.

### STORAGE

Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C)  
Shell may be stored in the dark for up to 5 years  
Do not store in direct / high heat or sunlight as this may distort the shell

### CLEANING

Clean using warm soapy water and soft cloth

Do not use solvents or abrasives

### WEIGHT

Slip fit - 320 grams

### PACKING

10 pieces per cartoon