





INDUSTRY Safety Gloves	IDEAL APPLICATIONS
Petrochemical	General handling
Automotive	Heavy material handling
Glass	General manual jobs
Construction	Oil & grease jobs
Machinery & equipment's	Raw material handling

## STANDARD : EN 388:2016

4542C





LINER TYPE		COATING		ADVANTAGE			
UHMWPE liner		Crinkled latex		Cut resistance & griping technology			
LINER COLOUR	CO	ATING COLOUR	COATIN	G TYPE	SIZE	CUFF	CERTIFICATION
Salt pepper	Blu	ue Crinkled palm coa			8 & 9	Normal overlocked	EN388 : 2016 – 4542C
FEATURES					APPLICATION		
UHMWPE ( ultra high molecular weight polyethylene ) cut level 5 / C liner				Assembly line, assembling metal parts and components Handling sharp or irregular metal pieces Molding, plastic injections STORAGE Store in cool and dry place Do not store in direct / high heat or sunlight Can be stored and transported in their original cartons			
Crinkled latex coating on palm							
Coating will give anti-slip performance and liner will provide cut level 5 / C protection							
Seamless knitted liner for ultimate comfort and higher flexibility				LAUNDERA Yes	ABLE PA	ACKING 20 pairs per carton	