

BL22

Safety Lanyard

STANDARD : CONFORMING TO EN 354:2010, EN 355:2002 CE

INDUSTRY	IDEAL APPLICATIONS
Construction	Work At Height
Metals & Mining	Ladder Climbing
Cement	Fall Arrest Rescue

SPECIAL FEATURES	
 LIGHT WEIGHT	 FALL RESTRAINT

ROPE MATERIAL
10.5mm Kernmantle Rope

FEATURES
Energy Absorbing Double Braided Rope Lanyard
One side (Lanyard End) connected with SH-60 scaffolding hook and on other side connected with EASY 308 Carabiner

CLEANING
Use clean piece of cloth to wipe the dust

PACKING
10 pieces per carton



STITCHING THREAD
High Tenacity Virgin Multifilament Polyester

BREAKING STRENGTH	LANYARD LENGTH
22kN (Min)	1.8 mm (Hook to Hook)

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacture
Material
Approvals & CE
Instruction Pictogram

STORAGE
Store the harness in a dry area away from ultraviolet rays.
Do not store in direct / high heat or sunlight as this may distort the Colour.
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.