





INDUSTRY	IDEAL APPLICATIONS
Work at a height	Suspend at a height, after arrest a fall.
Wind	
Power	
Construction	

SPECIAL FEATURES



MECHANICAL CHARACTERISTICS

Material: Durable polyester	
Webbing: 20mm wide	
Closures: Zipper fasteners	
Hook: Alloy steel with golden zinc plating	
Capacity: 141kg) Weight: 0.2 lbs. (91g)	
Length: Adjustable 1.1 m/1.0 m/0.9 m/0.8m/0.7m	
Weight: 200gm (Approx.)	

CLEANING Use clean piece of cloth to wipe the dust

PACKING 10 pieces per carton

FEATURES

The two packs are compact, lightweight and easily installed to most harness sizes, styles and brands.

After a fall, the packs can quickly be unzipped, deploying the web loop and hook straps which can easily be connected and adjusted to provide a strap for the foot to conveniently step into.

Length of the strap is adjustable at five size, can be adjust according to user comfort

This allows the worker to stand in their harness and relieve the pressure through the body while waiting for rescue.

Safety Strap Helps Prevent Suspension Trauma

STORAGE

Store the harness in a dry area away from ultraviolet rays. Do not store in direct / high heat or sunlight as this may distort the Colour.

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.

Tel.: +91 9820734624

E-mail: safety.vcare@gmail.com