




## EDGE NANO

Retractable Block

STANDARD : EN360:2002, ANSI Z359.14-2021, IS 3521(Part 3):2021

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES		
Construction	Working at Height	 FALL ARREST	 STRONG	 LIGHT WEIGHT
Process plants	Ladder Climbing			
Grinding Unit	Loading/Unloading point			
Manufacturing Unit	Bag House and vessels maintenance			

MECHANICAL CHARACTERISTICS	FEATURES
Webbing Material : UHMWPE Material (Ultra high molecular weight Poly Ethylene).	Has a Swivel Snap hook at one end and Swivel top to connect.
Static Strength: 20 kN	Extremely Compact, durable and light weight.
Average force less than : 4 kN	High capacity external shock absorber with impact indicator.
Fall Arrest Distance : 42 inch (Max.)	Quick-action breaking system.
Fall Arrest Force : 6 kN (Max.)	High strength anti corrosion components.
Safe Working Load : 140 kg	Combination of an energy absorbing unit, with connector. Connector opening 18 mm.
Free fall distance : 0.6 m (Max.)	Make of durable & light weight the lifeline made of webbing material.
Length : 1.8 m	
Weight : 1.295 kg	



MARKINGS	STORAGE
Manufacturers Logo, details & mailing address	Store the retractable in a dry area away from ultraviolet rays
Model No., Batch No., Serial No.	
Year of Manufacturing	Can be stored and transported in their original carton to avoid corrosion due to atmospheric moisture, excessive heat or cold
Material	
Instruction Pictogram	
CLEANING	PACKING
Use clean piece of cloth to wipe the dust	1 piece per box